



SAFETY DATA SHEET RAPIDE WIPES

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	RAPIDE WIPES
Internal identification	C055
UFI	UFI: DQ40-Q0NM-J00F-SYYQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cleaning agent.
Uses advised against	Use only for intended applications.

1.3. Details of the supplier of the safety data sheet

Supplier	ARROW SOLUTIONS RAWDON ROAD, MOIRA, SWADLINCOTE, DERBYSHIRE, DE12 6DA, ENGLAND TEL: +44 (0)1283 221044 sales@arrowchem.com
----------	--

1.4. Emergency telephone number

Emergency telephone	+44 (0) 777 8505 330 (24 hrs).
---------------------	--------------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards	Flam. Liq. 3 - H226
Health hazards	Not Classified
Environmental hazards	Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word	Warning
Hazard statements	H226 Flammable liquid and vapour. H411 Toxic to aquatic life with long lasting effects.

RAPIDE WIPES

Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves. P501 Dispose of contents/ container in accordance with national regulations.
Supplemental label information	EUH066 Repeated exposure may cause skin dryness or cracking.
UFI	UFI: DQ40-Q0NM-J00F-SYYQ
Detergent labelling	≥ 30% aliphatic hydrocarbons

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics	60-100%
CAS number: 90622-57-4	EC number: 923-037-2
Classification Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
2-(2-butoxyethoxy)ethanol	1-5%
CAS number: 112-34-5	EC number: 203-961-6
Classification Eye Irrit. 2 - H319	
2-butoxyethanol	1-5%
CAS number: 111-76-2	EC number: 203-905-0
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	
DIPROPYLENE GLYCOL n-BUTYL ETHER	1-5%
CAS number: 29911-28-2	EC number: 249-951-5
Classification Not Classified	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

RAPIDE WIPES

General information	Show this Safety Data Sheet to the medical personnel. If medical advice is needed, have product container or label at hand.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.
Skin contact	Rinse immediately with plenty of water. Wash skin thoroughly with soap and water. Get medical attention if symptoms are severe or persist.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Gastrointestinal symptoms, including upset stomach. Aspiration hazard if swallowed.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Eye contact	May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).

5.3. Advice for firefighters

Protective actions during firefighting	Use water to keep fire exposed containers cool and disperse vapours.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure procedures and training for emergency decontamination and disposal are in place. Keep unnecessary and unprotected personnel away from the spillage. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. No smoking, sparks, flames or other sources of ignition near spillage. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Avoid contact with skin, eyes and clothing. Do not touch or walk into spilled material. Avoid inhalation of vapours. Provide adequate ventilation. Take precautionary measures against static discharges. Avoid contact with contaminated tools and objects. Do not handle broken packages without protective equipment. Wash thoroughly after dealing with a spillage.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

RAPIDE WIPES

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Clean contaminated objects and areas thoroughly, observing environmental regulations. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Observe any occupational exposure limits for the product or ingredients. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Eliminate all sources of ignition. Provide adequate ventilation. Wear protective gloves. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Avoid release to the environment. Take precautionary measures against static discharge. During application and drying, solvent vapours will be emitted. Keep container tightly sealed when not in use. Do not eat, drink or smoke when using this product. Avoid contact with contaminated tools and objects. Do not handle broken packages without protective equipment. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store at temperatures between 4°C and 40°C. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage class

Flammable solid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics

Long-term exposure limit (8-hour TWA): WEL 1200 mg/m³ vapour

2-(2-butoxyethoxy)ethanol

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m³

Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m³

2-butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m³

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m³

Sk, BMGV

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

BMGV = Biological monitoring guidance value.

2-(2-butoxyethoxy)ethanol (CAS: 112-34-5)

RAPIDE WIPES

DNEL

Industry - Inhalation; : 101.2 mg/m³
 Industry - Dermal; : 20 mg/kg/day
 Industry - Inhalation; : 67.5 mg/m³
 Consumer - Inhalation; : 34 mg/m³
 Consumer - Dermal; : 10 mg/kg/day
 Consumer - Oral; : 1.25 mg/kg/day

PNEC

- Fresh water; 1 mg/l
- marine water; 0.1 mg/l
- Sediment (Freshwater); 4 mg/kg
- Sediment (Marinewater); 0.4 mg/kg
- Soil; 0.4 mg/kg
- STP; 200 mg/l

2-butoxyethanol (CAS: 111-76-2)

DNEL

Industry - Dermal; Short term systemic effects: 89 mg/kg/day
 Industry - Inhalation; Short term systemic effects: 663 mg/m³
 Industry - Dermal; Long term systemic effects: 75 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 98 mg/m³
 Consumer - Dermal; Short term systemic effects: 44.5 mg/kg
 Consumer - Inhalation; Short term systemic effects: 426 mg/m³
 Consumer - Oral; Short term systemic effects: 13.4 mg/m³
 Consumer - Dermal; Long term systemic effects: 38 mg/kg
 Consumer - Oral; Long term systemic effects: 3.2 mg/kg
 Consumer - Inhalation; Long term systemic effects: 49 mg/kg
 Consumer - Inhalation; local effects: 123 mg/kg
 Industry - Inhalation; local effects: 246 mg/m³

PNEC

- Fresh water; 8.8 mg/l
- marine water; 0.88 mg/l
- Sediment (Freshwater); 34.6 mg/kg
- Soil; 2.8 mg/kg
- STP; 463 mg/l
- Sediment (Marinewater); 3.46

DIPROPYLENE GLYCOL n-BUTYL ETHER (CAS: 29911-28-2)

DNEL

Professional - Dermal; Long term systemic effects: 3 mg/kg/day
 Professional - Inhalation; Long term systemic effects: 10 mg/m³
 Consumer - Dermal; Long term systemic effects: 1.1 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 1.2 mg/m³
 Consumer - Oral; Long term systemic effects: 7.5 mg/kg/day

PNEC

- Fresh water; 0.519 mg/l
- marine water; .0519 mg/l
- Sediment (Freshwater); 2.96 mg/kg
- Soil; 0.287 mg/kg
- STP; 100 mg/l
- Sediment (Marinewater); 0.296 mg/kg
- Intermittent release; 5.19 mg/l

8.2. Exposure controls

RAPIDE WIPES

Protective equipment



Appropriate engineering controls

Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment that provides appropriate eye and face protection should be worn. The following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, wear gloves that are proven to be impervious to the chemical and resist degradation. The selected gloves should have a breakthrough time of at least 4 hours. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. It should be noted that liquid may penetrate the gloves. Protective gloves should have a minimum thickness of 0.54 mm. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. The choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Repeated exposure to chemicals will degrade the ability of the glove to provide resistance to chemicals. Specific work environments and material handling practices may vary, therefore safety procedures should be developed for each intended application. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber. Thickness: > 0.54 mm

Hygiene measures

Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked. Half mask and quarter mask respirators with replaceable filter cartridges suitable for intended use should be used. Gas and combination filter cartridges suitable for intended use should be used. Particulate filters should comply with European Standard EN143. Disposable filtering half mask respirators suitable for intended use should be used. Change filter cartridge on respirator daily. Wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. Organic vapour + dust and mist filter.

Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Store in a demarcated bunded area to prevent release to drains and/or watercourses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid-impregnated wipe.
Colour	Colourless.

RAPIDE WIPES

Odour	Solvent.
pH	Not applicable.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	≥ 38°C Setaflash closed cup.
Evaporation rate	Not determined.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not applicable.
Vapour pressure	Not determined.
Relative density	~ 0.76 @ 25°C
Solubility(ies)	Slightly soluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not applicable.
Viscosity	Not applicable.
Explosive properties	There are no chemical groups present in the product that are associated with explosive properties.
Oxidising properties	There are no chemical groups present in the product that are associated with oxidising properties.
Comments	Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Other information Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Flammable/combustible materials.

10.6. Hazardous decomposition products

RAPIDE WIPES

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances:
Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 26,666.67

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 24,444.44

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Does not contain any substances known to be mutagenic.

Carcinogenicity

Carcinogenicity Does not contain any substances known to be carcinogenic.

Reproductive toxicity

Reproductive toxicity - fertility Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

Gastrointestinal symptoms, including upset stomach. Aspiration hazard if swallowed.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Eye contact

May cause discomfort.

Acute and chronic health hazards

Defatting, drying and cracking of skin. Headache.

RAPIDE WIPES

Route of exposure	Dermal Inhalation
Target organs	Central nervous system Skin
Medical symptoms	Dry skin. Headache.

Toxicological information on ingredients.

Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.1

Species Rat

ATE oral (mg/kg) 5,000.1

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,000.1

Species Rat

ATE dermal (mg/kg) 5,000.1

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ dust/mist mg/l) 5.1

Species Rat

ATE inhalation (dusts/mists mg/l) 5.1

2-butoxyethanol

Acute toxicity - oral

ATE oral (mg/kg) 1,200.0

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀)

DIPROPYLENE GLYCOL n-BUTYL ETHER

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,700.0

Species Rat

ATE oral (mg/kg) 3,700.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,001.0

RAPIDE WIPES

Species Rat

SECTION 12: Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish Not determined.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not determined.

Ecological information on ingredients.

Hydrocarbons, C10-C12, isoalkanes, < 2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1000 mg/kg, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₀, 48 hours: 1000 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₀, 72 hours: 1000 mg/l, Pseudokirchneriella subcapitata
NOEC, 72 hours: 1000 mg/l, Pseudokirchneriella subcapitata

Chronic aquatic toxicity

Chronic toxicity - aquatic invertebrates NOEC, 21 days: <1 mg/l, Daphnia magna

2-(2-butoxyethoxy)ethanol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 48 hours: 1820 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates NOEC, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants NOEC, 96 hours: >100 mg/l, Scenedesmus subspicatus

2-butoxyethanol

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 820 - 1490 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 835 - 1550 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 1840 mg/l, Algae

DIPROPYLENE GLYCOL n-BUTYL ETHER

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 841 mg/l, Poecilia reticulata (Guppy)

RAPIDE WIPES

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 1000 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is partly miscible with water and may spread in the aquatic environment.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

Special Provisions note

14.1. UN number

UN No. (ADR/RID) 3175

UN No. (IMDG) 3175

UN No. (ICAO) 3175

14.2. UN proper shipping name

Proper shipping name (ADR/RID) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(isoparaffinic hydrocarbon)

Proper shipping name (IMDG) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(isoparaffinic hydrocarbon)

Proper shipping name (ICAO) SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(isoparaffinic hydrocarbon)

14.3. Transport hazard class(es)

ADR/RID class 4.1

ADR/RID classification code F1

ADR/RID label 4.1

IMDG class 4.1

ICAO class/division 4.1

RAPIDE WIPES

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-I
ADR transport category	2
Emergency Action Code	1Z
Hazard Identification Number (ADR/RID)	40
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended).
Guidance	Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

RAPIDE WIPES

Abbreviations and acronyms used in the safety data sheet	<p>ATE: Acute Toxicity Estimate. ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. EC₅₀: 50% of maximal Effective Concentration. IATA: International Air Transport Association. IMDG: International Maritime Dangerous Goods. LC50: Lethal Concentration to 50 % of a test population. LD50: Lethal Dose to 50% of a test population (Median Lethal Dose). NOEC: No Observed Effect Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. PNEC: Predicted No Effect Concentration. REACH: The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577. UN: United Nations. vPvB: Very Persistent and Very Bioaccumulative.</p>
Classification abbreviations and acronyms	<p>Acute Tox. = Acute toxicity Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Skin Irrit. = Skin irritation</p>
Classification procedures according to SI 2019 No. 720	<p>Flam. Liq. 3 - H226: On basis of test data., Expert judgement. Aquatic Chronic 2 - H411: Calculation method.</p>
Revision comments	<p>NOTE: Lines within the margin indicate significant changes from the previous revision.</p>
Revision date	16/09/2022
Revision	4.2
Supersedes date	08/12/2020
SDS number	25317
Hazard statements in full	<p>H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.